

FDP3-35

Price Computing Scale

FDP3-35

Price Computing Scale

Features:

- 35 direct PLU keys
- High speed 24bits AD
- Faster display reading speed
- Faster weighing stability and zero return
- Zero key and Tare key react faster
- Vendor and customer sides LCD displays with LED backlight, double displays on tower
- LCD display full tare (Weight-6 digits, Unit Price-6 digits, Total Price-6 digits)
- Low power and charging status indication
- Built-in rechargeable battery
- Water channel designed underneath the platter to give a better protection against water running into the scale
- Unique rubber ring design to prevent dust, dirt, cockroaches and water intrusion into the scale for better reliability and hygiene
- Special power switch design to prevent moisture getting inside the scale for better performance, stability and reliability

■ Special sunken power coil outlet design to prevent water running into the socket to improve safety and reliability

■ Easily adjusted leveling feet for stability and the scale

Non-approval Model:

- 1/3,000 up to 1/6,000 display resolution, single range or multi-range
- Money change
- Kilogram (Kg) or pound (lb) weighing modes
- Up to 99 data accumulation and 25 data recall

Approval Model:

■ 1/3,000 display resolution, single range or multi-range

Options:

■ RS232 or serial printer output

Specifications:


| Model | Capacity | Division (single range) | Division (multi-range) |
|---------------|---------------|-------------------------|------------------------|
| FDP3-P-35 -3 | 3 kg (6 lb) | 1g (0.002 lb) | N/A |
| FDP3-P-35 -6 | 6 kg (12 lb) | 2g (0.005 lb) | 1g / 2g |
| FDP3-P-35 -15 | 15 kg (30 lb) | 5g (0.01 lb) | 2g / 5g |
| FDP3-P-35 -30 | 30 kg (60 lb) | 10g (0.02 lb) | 5g / 10g |

Operating Temperature: 0° C ~ 40° C (32° F ~ 104° F); Approval Model: -10° C ~ 40° C (14° F ~ 104° F)

Power Supply: AC 110/230V ±10% or DC 6V/4AH Rechargeable Battery

Dimentions: 300 x 530 x 330 mm (W x H x D)

Platter Size: 300 x 225 mm (W x D)





6F, No.127, Lane 235, Pao-Chiao Road, Hsin Tien, Taipei Hsien, 231, Taiwan Tel: +886-2-89191000 Website: www.excell-scale.com

E-mail: sales@excell-scale.com

Fax: +886-2-89191177

