



FM / FMR

Mini Indicator





FM / FMR

Mini Indicator

Features:

- Large LCD (digit height 25.4mm) display with LED backlight
- Kilogram (kg), pound (lb) and ton (T) weighing modes
- Auto zero tracking; Animal scale function; Data accumulation function
- Multi-range and multi-interval setting available
- Gravity value calibration
- Combination key for multi-functions
- Environmental filter setting for better performance
- High resolution switch function to display 10 times divisions
- Available in connecting with up to four 350-ohm load cells
- Capable of connecting with 6-wire load cells

Options:

- Rechargeable battery set (5pcs of DC 6V Ni-MH batteries in serial connection)
- Dry battery set (5pcs of 1.5V UM-3 dry battery)
- RS232/485 serial interface (switched by jumper) with RTC function



Black
Model



Red
Model



Specifications:

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F) ; Approval Model: -10°C ~ 40°C (14°F ~ 104°F)

Power Source: (1) Adaptor DC 9V + Ni-MH rechargeable battery set (2) Adaptor DC 9V + dry battery set

Dimensions: 193 x 134 x 49.5mm (W x H x D)

Display: LCD, 6 1/2 digits, height 25.4mm, LED backlight



EXCELL PRECISION CO., LTD.

6F, No.127, Lane 235, Pao-Chiao Road, Hsin Tien, Taipei Hsien, 231, Taiwan

Tel: +886-2-89191000

Website: www.excell-scale.com

Fax: +886-2-89191177

E-mail: sales@excell-scale.com